



284WMT\_PM6 WR284 Waveguide Magic Tee 2.6-3.95GHz with Four Rectangular Waveguide Interfaces

WR284 Waveguide Magic Tee Operating From 2.6 to 3.95GHz with Four Rectangular Waveguide Interfaces

### Product Information

SKU	284WMT_PM6
-----	------------

### Description

Waveguide magic tee 284WMT\_PM6, operating from 2.6 to 3.95GHz with a 0.4dB insertion loss, 40dB isolation, H-Plane VSWR 1.30:1 and E-Plane VSWR 1.50:1. 284WMT\_PM6 is a four-ports hybrid coupler or power divider. All the ports have standard WR284 waveguides with the same flanges FDP32(UDR32). The magic tee can be used as a power combiner or a power divider based on the given application's needs.

### Technical Specification

Electrical Specification		Interface	
WG Tee Type	Magic Tee	Flange 3 Style	Rectangular
Waveguide Band	S	Flange 3 Type	Cover
Waveguide Type	Rectangular	Flange 3 Designation	FDP32(UDR32)
Waveguide Size EIA WR	WR284	Flange 4 Style	Rectangular
Frequency, Min (GHz)	2.6	Flange 4 Type	Cover
Frequency, Max (GHz)	3.95	Flange 4 Designation	FDP32(UDR32)
I.L., Typ (dB)	0.4	Mechanical Specification	
I.L., Max (dB)	0.6	Body Material	Al
VSWR, H-Plane, Typ	1.3	Size, L (mm)	177.8
VSWR, H-Plane, Typ	1.30:1	Size, W (mm)	146.1
VSWR, E-Plane, Typ	1.5	Size, H (mm)	149.6
VSWR, E-Plane, Typ	1.50:1	Weight, (kg)	0.99
Isolation, Min (dB)	30	Pressure Sealed	No
Isolation, Typ (dB)	40	Environmental Specification	
Power Handling, CW, (W)	4800	Operating Temp. Low (°C)	-55
<b>Interface</b>		Operating Temp. High (°C)	85
Flange 1 Style	Rectangular	Storage Temp. Low (°C)	-60
Flange 1 Type	Cover	Storage Temp. High (°C)	90
Flange 1 Designation	FDP32(UDR32)		
Flange 2 Style	Rectangular		
Flange 2 Type	Cover		
Flange 2 Designation	FDP32(UDR32)		

### Additional Information

Application	General Purpose Indoor & Outdoor, Fixed
-------------	---

### Similar Products



229WET WR229 Waveguide E-Plane Tee 3.3-4.9GHz with Three Rectangular Waveguide Interfaces



229WHT WR229 Waveguide H-Plane Tee 3.3-4.9GHz with Three Rectangular Waveguide Interfaces



229WMT WR229 Waveguide Magic Tee 3.3-4.9GHz with Four Rectangular Waveguide Interfaces



284WET WR284 Waveguide E-Plane Tee 2.6-3.95GHz with Three Rectangular Waveguide Interfaces



284WHT WR284 Waveguide H-Plane Tee 2.6-3.95GHz with Three Rectangular Waveguide Interfaces



284WMT WR284 Waveguide Magic Tee 2.6-3.95GHz with Four Rectangular Waveguide Interfaces



284WMT\_PM5 WR284 Waveguide Magic Tee 2.6-3.95GHz with Four Rectangular Waveguide Interfaces



340WET WR340 Waveguide E-Plane Tee 2.2-3.3GHz with Three Rectangular Waveguide Interfaces



340WHT WR340 Waveguide H-Plane Tee 2.2-3.3GHz with Three Rectangular Waveguide Interfaces



340WMT WR340 Waveguide Magic Tee 2.2-3.3GHz with Four Rectangular Waveguide Interfaces

### About this Datasheet

<ul style="list-style-type: none"> <li>● <b>Product Information</b> Product Link: <a href="https://www.ainfoinc.com/284wmt-pm6-wr284-waveguide-magic-tee-2-6-3-95-ghz-fdp32-udr32">https://www.ainfoinc.com/284wmt-pm6-wr284-waveguide-magic-tee-2-6-3-95-ghz-fdp32-udr32</a> Data subject to change without notice. © A-INFO INC. 2024. All Rights Reserved</li> </ul>	<ul style="list-style-type: none"> <li>● <b>Contact Us</b> Address: 60 Tesla, Irvine, CA 92618, USA Website: <a href="http://www.ainfoinc.com">www.ainfoinc.com</a> Email: <a href="mailto:sales@ainfoinc.com">sales@ainfoinc.com</a></li> </ul>	<ul style="list-style-type: none"> <li>● <b>Phone &amp; Fax</b> Phone: +1-949-639-9688 +1-949-639-9608 Fax: +1-949-639-9670</li> </ul>
---	--	--