



DC COMPONENTS CO., LTD.

RECTIFIER SPECIALISTS

**KBL / RS
005 / 401
THRU
KBL / RS
10 / 407**

TECHNICAL SPECIFICATIONS OF SINGLE-PHASE SILICON BRIDGE RECTIFIER

VOLTAGE RANGE - 50 to 1000 Volts

CURRENT - 4.0 Amperes

FEATURES

- * Ideal for printed circuitboard
- * Surge overload rating:125 Amperes peak
- * Molded structure
- * Glass passivated juncton

MECHANICAL DATA


- * Case: Molded plastic
- * Epoxy: UL 94V-0 rate flame retardant
- * Lead: MIL-STD-202E, Method 208 guaranteed
- * Polarity: Symbols molded or marked on body
- * Mounting: position: Any
- * Weight: 4.8 grams

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25 °C ambient temperature unless otherwise specified.
Single phase, half wave, 60 Hz, resistive or inductive load.
For capacitive load, derate current by 20%.



KBL



		KBL005	KBL01	KBL02	KBL04	KBL06	KBL08	KBL10	
SYMBOL		RS401	RS402	RS403	RS404	RS405	RS406	RS407	UNITS
Maximum Recurrent Peak Reverse Voltage		50	100	200	400	600	800	1000	Volts
Maximum RMS Bridge Input Voltage		35	70	140	280	420	560	700	Volts
Maximum DC Blocking Voltage		50	100	200	400	600	800	1000	Volts
Maximum Average Forward Output Current at $T_A = 50^\circ\text{C}$		4.0							Amps
Peak Forward Surge Current 8.3 ms single half sine-wave superimposed on rated load (JEDEC Method)		125							Amps
Maximum Forward Voltage Drop per element at 4.0 A DC		1.1							Volts
Maximum DC Reverse Current at Rated DC Blocking Voltage per element	@ $T_J = 25^\circ\text{C}$	10							uAmps
	@ $T_J = 100^\circ\text{C}$	500							
Operating Temperature Range		-55 to + 150							$^\circ\text{C}$
Storage Temperature Range		-55 to + 150							$^\circ\text{C}$

RATING AND CHARACTERISTIC CURVES (KBL005 THRU KBL10 RS401 THRU RS407)

FIG. 1 - MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG. 2 - TYPICAL FORWARD CURRENT DERATING CURVE




FIG. 3 - TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS





FIG. 4 - TYPICAL REVERSE CHARACTERISTICS



Disclaimer

Any Customer or user of this document or products described herein in such applications shall assume all risks of such use and will agree to hold *DC COMPONENTS* harmless against all damages.

DC COMPONENTS disclaims any and all liability arising out of the application or use of any product, including consequential or incidental damages. Statement regarding the suitability of products for certain types of applications are based on *DC COMPONENTS*'s knowledge of typical requirements that are often placed on *DC COMPONENTS* products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application.

DC COMPONENTS reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein, and disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product. Parameters provided in datasheets and specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify *DC COMPONENTS*'s terms and conditions of purchase, including but not limited to the warranty expressed therein.

Unless otherwise in writing, *DC COMPONENTS* products are intended for use as general electronic components in standard applications (eg: Consumer electronic, Computer equipment, Office equipment, etc.), and not recommended for use in a high specific application where a failure or malfunction of the device could result in human injury or death (eg: Aerospace equipment, Submarine cables, Combustion equipment, Safety devices, Life support systems, etc.)

Customers using or selling *DC COMPONENTS* products not expressly indicated for use in such applications do so at their own risk. If customer intended to use *DC COMPONENTS* standard quality grade devices for applications not envisioned by *DC COMPONENTS*, please contact our sales representatives in advance.



DC COMPONENTS CO., LTD.