



Technical Specification



Frequency Range(GHz)	2.60 - 3.95
Gain(dB)	20 Typ.
3dB Beamwidth(deg)	18 Typ.
Waveguide	WR284
Material	Al
Output	A Type: FDP32(UDR32)C Type: N-F or SMA-F or 7/16-F
Size(mm)	A Type: 405x325x550 C Type: 405x325x629
Net Weight(Kg)	A Type: 3.2 Around C Type: 3.6 Around


Outline Drawing (Size: mm)

A Type (With FDP32 Output)




C Type (With N type Female Output)

For SMA-Female or 7/16-Female output outline drawing, please contact A-INFO.




C Type (With N type Female Output & Round Mounting Bracket)

For SMA-Female or 7/16-Female output outline drawing, please contact A-INFO.





C Type (With N type Female Output & L Type Mounting Bracket)

For SMA-Female or 7/16-Female output outline drawing, please contact A-INFO.



A Type (With Radome)



AINFO Inc.

Page 3 of 10

China(Beijing):
China(Chengdu):
USA :

Tel: (+86) 10-6266-7326,
Tel: (+86) 28-8519-2786,
Tel: (+1) 949-639-9688,


(+86) 10-6266-7327
(+86) 28-8519-3044
(+1) 949-639-9608

Fax: (+86) 10-6266-7379
Fax: (+86) 28-8519-3068
Fax: (+1) 949-639-9670

Website: www.ainfoinc.com
Email: sales@ainfoinc.com


C Type (With N type Female Output & Radome)

For SMA-Female or 7/16-Female output outline drawing, please contact A-INFO.




C Type (With N type Female Output & Round Mounting Bracket & Radome)

For SMA-Female or 7/16-Female output outline drawing, please contact A-INFO.




C Type (With N type Female Output & L Type Mounting Bracket & Radome)

For SMA-Female or 7/16-Female output outline drawing, please contact A-INFO.



Flange Drawing (Size: mm)



FDP32

AINFO Inc.

Page 6 of 10

China(Beijing):
China(Chengdu):
USA :

Tel: (+86) 10-6266-7326,
Tel: (+86) 28-8519-2786,
Tel: (+1) 949-639-9688,



(+86) 10-6266-7327
(+86) 28-8519-3044
(+1) 949-639-9608

Fax: (+86) 10-6266-7379
Fax: (+86) 28-8519-3068
Fax: (+1) 949-639-9670

Website: www.ainfoinc.com
Email: sales@ainfoinc.com


Test Results

1. Gain and Antenna Factor




Frequency(GHz)	Gain(dB)	Antenna Factor(dB/m)
2.60	18.68	19.83
2.70	18.99	19.85
2.80	19.16	19.99
2.90	19.45	20.00
3.00	19.56	20.19
3.10	19.69	20.35
3.20	19.83	20.48
3.30	19.95	20.63
3.40	20.11	20.73
3.50	20.32	20.77
3.60	20.35	20.99
3.70	20.48	21.09
3.80	20.62	21.18
3.90	20.53	21.50
3.95	20.52	21.62

2. VSWR



3. Cross Polarization Isolation



4. Pattern

