

62WLPL_P0 WR62 Waveguide Low Power Load 12.4-18GHz with Rectangular Waveguide Interface

WR62 Waveguide Low Power Load Operating From 12.4 to 18GHz with Rectangular Waveguide Interface



Product Information

SKU	62WLPL_P0
-----	-----------

Description

Waveguide low power load 62WLPL_P0, operating from 12.4 to 18GHz and low VSWR 1.04:1 62WLPL_P0 covers the WR62 full waveguide band and comes with one flange APF62. It can handle 1.5W continuously and 1.5KW peak power. The WLPL series are for general version, low VSWR terminations for system application. The typical applications include system or test bench set-ups and small moderate power dummy loads.

Technical Specification

Electrical Specification		Mechanical Specification	
WG Load Type	Low Power	Body Material	Al
Waveguide Band	Ku	Size, L (mm)	102
Waveguide Type	Rectangular	Size, W (mm)	33.3
Waveguide Size EIA WR	WR62	Size, H (mm)	33.3
Frequency, Min (GHz)	12.4	Weight, (kg)	0.05
Frequency, Max (GHz)	18	Pressure Sealed	No
VSWR, Typ	1.03:1	Environmental Specification	
VSWR, Max	1.04:1	Operating Temp. Low (°C)	-55
Power Handling, CW, (W)	1.5	Operating Temp. High (°C)	85
Power Handling, Peak, (KW)	1.5	Storage Temp. Low (°C)	-60
		Storage Temp. High (°C)	90
Interface			
Flange Style	Square		
Flange Type	Cover		
Flange Designation	APF62		

Additional Information

Application	General Purpose Indoor & Outdoor, Fixed
-------------	---

About this Datasheet

<ul style="list-style-type: none"> ● Product Information Product Link: https://www.ainfoinc.com/62wplp-p0-wr62-waveguide-low-power-load-12-4-18-ghz-apf62 Data subject to change without notice. © A-INFO INC. 2024. All Rights Reserved 	<ul style="list-style-type: none"> ● Contact Us Address: 60 Tesla, Irvine, CA 92618, USA Website: www.ainfoinc.com Email: sales@ainfoinc.com 	<ul style="list-style-type: none"> ● Phone & Fax Phone: +1-949-639-9688 +1-949-639-9608 Fax: +1-949-639-9670
---	--	--