

2W – N DC-8GHz Coaxial Attenuator

Design Features

- ◆ High RF performance, ultra-competitive price.
- ◆ Military, space and commercial applications.
- ◆ Custom design available upon request.
- ◆ Support one year standard warranty.

RF Characteristics


Model Number	Freq. Range	Power	Attenuation Value	Attenuation Tolerance	VSWR Max	Connector Type	Impedance
UIYCA2AN8A1	DC-8GHz	2W	1 dB	±0.5 dB	1.3	N-M / N-F	50 Ω
UIYCA2AN8A2	DC-8GHz	2W	2 dB	±0.5 dB	1.3	N-M / N-F	50 Ω
UIYCA2AN8A3	DC-8GHz	2W	3 dB	±0.5 dB	1.3	N-M / N-F	50 Ω
UIYCA2AN8A5	DC-8GHz	2W	5 dB	±0.5 dB	1.3	N-M / N-F	50 Ω
UIYCA2AN8A6	DC-8GHz	2W	6 dB	±0.5 dB	1.3	N-M / N-F	50 Ω
UIYCA2AN8A10	DC-8GHz	2W	10 dB	±0.5 dB	1.3	N-M / N-F	50 Ω
UIYCA2AN8A15	DC-8GHz	2W	15 dB	±0.5 dB	1.3	N-M / N-F	50 Ω
UIYCA2AN8A20	DC-8GHz	2W	20 dB	±0.5 dB	1.3	N-M / N-F	50 Ω
UIYCA2AN8A30	DC-8GHz	2W	30 dB	±0.6 dB	1.3	N-M / N-F	50 Ω
UIYCA2AN8A40	DC-8GHz	2W	40 dB	±0.8dB	1.3	N-M / N-F	50 Ω
UIYCA2AN8A50	DC-8GHz	2W	50 dB	±1.0dB	1.3	N-M / N-F	50 Ω

² Listed are specific frequency ranges and tailor-made ranges are available.

² Please provide the information below when inquiring and mark * is required.

- * 1. Power handling, Attenuation Value
- 2. Connect type (SMA Male/ Female, N Male/ Female, etc.)
- 3. Other special requests (VSWR, Temperature, Dimension, etc.)

Mechanical Drawing



Unit: mm/ inch, General part tolerance is ±2% unless otherwise stated.

Ver. 5.1