

High efficiency rectifier

Features

- Ultrafast recovery
- Low power losses
- High surge capability
- Low leakage current
- High junction temperature

Description

The STTH1003S is an ultrafast recovery power rectifier dedicated to energy recovery in PDP applications.

It is especially designed for clamping function in energy recovery block. The compromise between forward voltage drop and recovery time offers optimized performances.




Table 1. Device summary

| | |
|----------------|--------|
| $I_{F(AV)}$ | 10 A |
| V_{RRM} | 300 V |
| t_{rr} (typ) | 13 ns |
| T_j | 175 °C |
| V_F (typ) | 0.9 V |

1 Characteristics

Table 2. Absolute ratings (limiting values)

| Symbol | Parameter | Value | Unit | |
|-------------|--|--|------------------|---|
| V_{RRM} | Repetitive peak reverse voltage | 300 | V | |
| $I_F(RMS)$ | Forward rms current | 20 | A | |
| $I_{F(AV)}$ | Average forward current | $T_c = 150 \text{ } ^\circ\text{C} \quad \delta = 0.5$ | A | |
| I_{FSM} | Surge non repetitive forward current | $t_p = 10 \text{ ms sinusoidal}$ | 100 | A |
| I_{RSM} | Non repetitive avalanche current | $t_p = 20 \mu\text{s square}$ | 4 | A |
| T_{stg} | Storage temperature range | -65 to + 175 | $^\circ\text{C}$ | |
| T_j | Maximum operating junction temperature | 175 | $^\circ\text{C}$ | |

Table 3. Thermal resistance

| Symbol | Parameter | Package | Value | Unit |
|---------------|------------------|--------------------------|-------|--------------------|
| $R_{th(j-c)}$ | Junction to case | DPAK, D ² PAK | 4 | $^\circ\text{C/W}$ |
| | | TO-220FPAB | 6 | |

Table 4. Static electrical characteristics

| Symbol | Parameter | Test conditions | | Min. | Typ | Max. | Unit |
|-------------|-------------------------|-------------------------------------|----------------------|------|-----|------|---------------|
| $I_R^{(1)}$ | Reverse leakage current | $T_j = 25 \text{ } ^\circ\text{C}$ | $V_R = V_{RRM}$ | - | - | 10 | μA |
| | | $T_j = 125 \text{ } ^\circ\text{C}$ | | - | 10 | 100 | |
| $V_F^{(2)}$ | Forward voltage drop | $T_j = 25 \text{ } ^\circ\text{C}$ | $I_F = 10 \text{ A}$ | - | - | 1.30 | V |
| | | $T_j = 125 \text{ } ^\circ\text{C}$ | | - | 0.9 | 1.1 | |

1. Pulse test: $t_p = 5 \text{ ms}, \delta < 2 \%$ 2. Pulse test: $t_p = 380 \mu\text{s}, \delta < 2 \%$

To evaluate the conduction losses use the following equation:

$$P = 0.86 \times I_{F(AV)} + 0.024 I_F^2 (\text{RMS})$$

Table 5. Recovery characteristics

| Symbol | Parameter | Test conditions | | | Min. | Typ | Max. | Unit |
|--------------|--------------------------|---------------------------|--|---|------|-----|------|------|
| t_{rr} | Reverse recovery time | $T_j = 25^\circ\text{C}$ | $I_F = 0.5 \text{ A}$, $I_{rr} = 0.25 \text{ A}$, $I_R = 1 \text{ A}$ | - | 13 | 17 | ns | |
| | | | $I_F = 1 \text{ A}$, $V_R = 30 \text{ V}$ $dI_F/dt = -50 \text{ A}/\mu\text{s}$ | - | 28 | 35 | | |
| t_{fr} | Forward recovery time | $T_j = 25^\circ\text{C}$ | $I_F = 10 \text{ A}$, $dI_F/dt = 100 \text{ A}/\mu\text{s}$ $V_{FR} = 1.1 \times V_{Fmax}$ | - | - | 200 | ns | |
| V_{FP} | Peak forward voltage | $T_j = 25^\circ\text{C}$ | $I_F = 10 \text{ A}$, $dI_F/dt = 100 \text{ A}/\mu\text{s}$ | - | 2.5 | 3.5 | V | |
| I_{RM} | Reverse recovery current | $T_j = 125^\circ\text{C}$ | $I_F = 10 \text{ A}$, $V_{CC} = 200 \text{ V}$ | - | 5.7 | 7.5 | A | |
| S_{factor} | Softness factor | | $dI_F/dt = 200 \text{ A}/\mu\text{s}$ | - | 0.3 | - | | |





Figure 1. Forward voltage drop versus current (maximum values)**Figure 2. Peak reverse recovery current versus dI_F/dt (90% confidence)****Figure 3. Reverse recovery time versus dI_F/dt (90% confidence)****Figure 4. Softness factor versus dI_F/dt (typical values)**

Figure 5. Relative variations of dynamic parameters versus junction temperature (reference: $T_j = 125^\circ\text{C}$)




Figure 6. Transient peak forward voltage versus dI_F/dt (90% confidence)





Figure 7. Forward recovery time versus dI_F/dt (90% confidence)



2 Package information

- Epoxy meets UL94, V0
- Cooling method: by conduction
- Recommended torque value: 0.4 to 0.6 N·m.

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: www.st.com.
ECOPACK® is an ST trademark.

Table 6. DPAK dimensions

| Ref. | Dimensions | | | |
|------|-------------|-------|------------|-------|
| | Millimeters | | Inches | |
| | Min. | Max. | Min. | Max. |
| A | 2.20 | 2.40 | 0.086 | 0.094 |
| A1 | 0.90 | 1.10 | 0.035 | 0.043 |
| A2 | 0.03 | 0.23 | 0.001 | 0.009 |
| B | 0.64 | 0.90 | 0.025 | 0.035 |
| B2 | 5.20 | 5.40 | 0.204 | 0.212 |
| C | 0.45 | 0.60 | 0.017 | 0.023 |
| C2 | 0.48 | 0.60 | 0.018 | 0.023 |
| D | 6.00 | 6.20 | 0.236 | 0.244 |
| E | 6.40 | 6.60 | 0.251 | 0.259 |
| G | 4.40 | 4.60 | 0.173 | 0.181 |
| H | 9.35 | 10.10 | 0.368 | 0.397 |
| L2 | 0.80 typ. | | 0.031 typ. | |
| L4 | 0.60 | 1.00 | 0.023 | 0.039 |
| V2 | 0° | 8° | 0° | 8° |

Figure 8. Footprint (dimensions in mm)




Table 7. D²PAK dimensions

| Ref. | Dimensions | | | | | |
|------|-------------|------|-------|--------|-------|-------|
| | Millimeters | | | Inches | | |
| | Min. | Typ. | Max. | Min. | Typ. | Max. |
| A | 4.30 | | 4.60 | 0.169 | | 0.181 |
| A1 | 2.49 | | 2.69 | 0.098 | | 0.106 |
| A2 | 0.03 | | 0.23 | 0.001 | | 0.009 |
| B | 0.70 | | 0.93 | 0.027 | | 0.037 |
| B2 | 1.25 | 1.40 | | 0.048 | 0.055 | |
| C | 0.45 | | 0.60 | 0.017 | | 0.024 |
| C2 | 1.21 | | 1.36 | 0.047 | | 0.054 |
| D | 8.95 | | 9.35 | 0.352 | | 0.368 |
| E | 10.00 | | 10.28 | 0.393 | | 0.405 |
| G | 4.88 | | 5.28 | 0.192 | | 0.208 |
| L | 15.00 | | 15.85 | 0.590 | | 0.624 |
| L2 | 1.27 | | 1.40 | 0.050 | | 0.055 |
| L3 | 1.40 | | 1.75 | 0.055 | | 0.069 |
| R | 0.40 | | | 0.016 | | |
| V2 | 0° | | 8° | 0° | | 8° |


Figure 9. Footprint (dimensions in mm)

Table 8. TO-220FPAB dimensions

| Ref. | Dimensions | | | |
|------|-------------|------|-----------|-------|
| | Millimeters | | Inches | |
| | Min. | Max. | Min. | Max. |
| A | 4.4 | 4.6 | 0.173 | 0.181 |
| B | 2.5 | 2.7 | 0.098 | 0.106 |
| D | 2.5 | 2.75 | 0.098 | 0.108 |
| E | 0.45 | 0.70 | 0.018 | 0.027 |
| F | 0.75 | 1 | 0.030 | 0.039 |
| F1 | 1.15 | 1.50 | 0.045 | 0.059 |
| F2 | 1.15 | 1.50 | 0.045 | 0.059 |
| G | 4.95 | 5.20 | 0.195 | 0.205 |
| G1 | 2.4 | 2.7 | 0.094 | 0.106 |
| H | 10 | 10.4 | 0.393 | 0.409 |
| L2 | 16 Typ. | | 0.63 Typ. | |
| L3 | 28.6 | 30.6 | 1.126 | 1.205 |
| L4 | 9.8 | 10.6 | 0.386 | 0.417 |
| L5 | 2.9 | 3.6 | 0.114 | 0.142 |
| L6 | 15.9 | 16.4 | 0.626 | 0.646 |
| L7 | 9.00 | 9.30 | 0.354 | 0.366 |
| Dia. | 3.00 | 3.20 | 0.118 | 0.126 |

3 Ordering information

Table 9. Ordering information

| Order code | Marking | Package | Weight | Base qty | Delivery mode |
|---------------|-----------|--------------------|--------|----------|---------------|
| STTH1003SFP | STTH1003S | TO-220FPAB | 1.70 g | 50 | Tube |
| STTH1003SB | STTH1003S | DPAK | 0.3 g | 75 | Tube |
| STTH1003SB-TR | STTH1003S | | | 2500 | Tape and reel |
| STTH1003SG | STTH1003S | D ² PAK | 1.48 g | 50 | Tube |
| STTH1003SG-TR | STTH1003S | | | 1000 | Tape and reel |

4 Revision history

Table 10. Document revision history

| Date | Revision | Changes |
|-------------|----------|--|
| 24-Aug-2005 | 1 | First issue. |
| 18-May-2009 | 2 | Reformatted to current standards. Modified configuration diagram on front page. Update dimensions F1 and F2 in Table 8 . |

Please Read Carefully:

Information in this document is provided solely in connection with ST products. STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, modifications or improvements, to this document, and the products and services described herein at any time, without notice.

All ST products are sold pursuant to ST's terms and conditions of sale.

Purchasers are solely responsible for the choice, selection and use of the ST products and services described herein, and ST assumes no liability whatsoever relating to the choice, selection or use of the ST products and services described herein.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted under this document. If any part of this document refers to any third party products or services it shall not be deemed a license grant by ST for the use of such third party products or services, or any intellectual property contained therein or considered as a warranty covering the use in any manner whatsoever of such third party products or services or any intellectual property contained therein.

UNLESS OTHERWISE SET FORTH IN ST'S TERMS AND CONDITIONS OF SALE ST DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY WITH RESPECT TO THE USE AND/OR SALE OF ST PRODUCTS INCLUDING WITHOUT LIMITATION IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION), OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.

UNLESS EXPRESSLY APPROVED IN WRITING BY AN AUTHORIZED ST REPRESENTATIVE, ST PRODUCTS ARE NOT RECOMMENDED, AUTHORIZED OR WARRANTED FOR USE IN MILITARY, AIR CRAFT, SPACE, LIFE SAVING, OR LIFE SUSTAINING APPLICATIONS, NOR IN PRODUCTS OR SYSTEMS WHERE FAILURE OR MALFUNCTION MAY RESULT IN PERSONAL INJURY, DEATH, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE. ST PRODUCTS WHICH ARE NOT SPECIFIED AS "AUTOMOTIVE GRADE" MAY ONLY BE USED IN AUTOMOTIVE APPLICATIONS AT USER'S OWN RISK.

Resale of ST products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by ST for the ST product or service described herein and shall not create or extend in any manner whatsoever, any liability of ST.

ST and the ST logo are trademarks or registered trademarks of ST in various countries.

Information in this document supersedes and replaces all information previously supplied.

The ST logo is a registered trademark of STMicroelectronics. All other names are the property of their respective owners.

© 2009 STMicroelectronics - All rights reserved

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Philippines - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

www.st.com

